

Application No.: 10/658,338

Inventor: Bosse

Response to O.A. dated February 5, 2007

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

Claims 1-13 (canceled)

Claim 14 (new): A lock removal tool, comprising:

an elongated bar having a first end and a second end;

a lock cutting tool disposed on the first end of said bar, the lock cutting tool being a generally rectangular, flat plate having leading and trailing edges and top and bottom surfaces, said bar being joined to the lock cutting tool generally between the leading and trailing edges, said bar being angled away from the top surface and extending rearward from the lock cutting tool;

a tool piece extending from the second end of said bar axially aligned with said bar;

a first impact collar disposed on said bar near the first end and substantially near said trailing edge of said lock cutting tool, so as to form a space between said first impact collar and said trailing edge of said lock cutting tool to accommodate a metal bar;

a second impact collar disposed on said bar near the second end; and

a weight slidably disposed on said bar between the first and the second impact collars.

Application No.: 10/658,338

Inventor: Bosse

Response to O.A. dated February 5, 2007

Claim 15 (new): The lock removal tool according to claim 14, wherein said tool piece comprises a length of metal stock.

Claim 16 (new): The lock removal tool according to claim 14, wherein said metal stock is square.

Claim 17 (new): The lock removal tool according to claim 14, wherein said metal stock is tapered to define a blade.

Claim 18 (new): The lock removal tool according to claim 14, wherein the second end of said bar has a tool piece receptacle defined therein and a threaded set screw aperture formed through the bar and extending into the receptacle, the lock removal tool further comprising a set screw engaging the set screw aperture, whereby said tool piece is removably retained within said tool piece receptacle by said set screw.

Claim 19 (new): The lock removal tool according to claim 14, wherein the leading edge of said lock cutting tool is bifurcated to form a cutting slot, the cutting slot being a generally "V" shaped slot having inner edges.

Claim 20 (new): The lock removal tool according to claim 14, wherein said top surface of said lock cutting tool is tapered along the leading edge.

Application No.: 10/658,338

Inventor: Bosse

Response to O.A. dated February 5, 2007

Claim 21 (new): The lock removal tool according to claim 14, wherein the leading edge of said lock cutting tool is bifurcated to form a cutting slot, the cutting slot being a generally "V" shaped slot having inner edges, the top surface of said cutting tool being tapered along the inner edges of said cutting slot.

Claim 22 (new): The lock removal tool according to claim 14, wherein the top surface of said lock cutting tool is tapered along the trailing edge.

Claim 23 (new): The lock removal tool according to claim 14, wherein the bottom surface of said cutting tool is curved at the leading edge.

Claim 24 (new): The lock removal tool according to claim 14, wherein said cutting tool has at least one groove formed in the top surface, the at least one groove extending transversely across the top surface.

Claim 25 (new): The lock removal tool according to claim 14, wherein said cutting tool has at least one groove formed in the bottom surface, the at least one groove extending transversely across the bottom surface.

Application No.: 10/658,338

Inventor: Bosse

Response to O.A. dated February 5, 2007

Claim 26 (new): The lock removal tool according to claim 14, wherein said bar and said lock cutting tool are joined at an angle of between 15° and 45°.